Volume : 4 | Issue : 7 | July 2015 • ISSN No 2277 - 8179

Research Paper

Rebroadcasting for Minimization of Routing Based upon Neighbor Coverage in MANET's

Engineering

KEYWORDS : Routing Over Head, Packet Delay, Packet Delivery Ratio

Dr. M. Nagaratna — Assistant Professor, Department of CSE, JNTUH College of Engineering, Kukatpally, Hyderabad, Telangana, India

V NarasimhaRao Guttula — M.Tech Student, Department of CSE, JNTUH College of Engineering, Kukatpally, Hyderabad, Telangana, India

ABSTRACT

In mobile ad hoc networks the nodes are in mobile nature for that reason frequent link breakages will occur, which causes frequent route discoveries and path failures. In Route discovery broadcasting is the most important concept, Initially in a network all the nodes receive the route request packets apart from the destination, route, as a result it starts the broadcast storm problem. In this, we explored a protocol based on probabilistic rebroadcast mechanism that is predicated on neighbor coverage, decreasing routing located in MANETs. So based on the neighbor coverage information, we proposed a piece of fiction rebroadcast rearrangement to get the rebroadcast procedure, by sensing the neighbor coverage information, rebroadcast covers the most of the nodes that is we will get more additional coverage ratio of the nodes. By using additional coverage ratio we get the better rebroadcast procedure. This procedure mingles the advantages of the probabilistic mechanism and neighbor coverage information, which can significantly reduce the count of the retransmissions and therefore it minimizes routing overhead and it improves the routing routine.

INTRODUCTION

MANETs (MOBILE ad hoc networks) contains a collection of mobile nodes which are moves without restraint. These nodes can be enthusiastically self-organized into topology networks which are arbitrary without a predetermined infrastructure. One of the MANETs primary challenges is the dynamic routing protocols design with fine routine and less overhead. A lot of routing protocols, like DSR (Dynamic Source Routing) [1], and AODV Routing (Ad hoc On-demand Distance Vector) [2]have been projected for MANETs. The couple of protocols which are mentioned above are on-demand routing protocols and when a new route is requested by restraining the routing overhead [3] they can improve the scalability of the MANETs. Though in the MANETs because of node mobility, frequent link breakages may lead to frequent route discoveries and path breakdowns, which could increase the routing protocols over ahead and delay of the end to end transaction and also reduces the ratio of packet delivery.

The route discovered in conventional on- demand routing protocols is by using broadcasting. RREQ (Route REQuest) packet was broadcasted to the networks, and the excessive redundant retransmissions was persuaded by broadcasting of Route REQuest packet and creates the broadcast storm crisis [4], In large number of networks it leads to more number of packet collisions. So it is necessary to optimize the broadcast mechanism. In MANETS for the past few years some methods are proposed to optimize the broadcast crisis. Broadcasting protocols are categorized into four classes i.e. "probability-based, simple flooding, neighbor knowledge, and area based." In Static networks, if the number of nodes are increases then the performances are decreases by using area-based and probability-based methods [5]. The performance of neighor knowledge is better than the area based methods and area based is better than the probability based[6].

PROBLEM STATEMENT

Since restraining the rebroadcasts count can effectively performs broadcasting optimization, and therefore the performance of neighbor information schemes better than the area-based schemes and the probability-based schemes.

By using neighbor coverage information we can find the order of rebroadcast, connectivity factor. By using the connectivity factor we can find number of neighbors (neighbors should receive the route request packets), network connectivity and reduce redundant retransmissions. Additional coverage ratio and connectivity factor are used to improve the performance of the routing and to decrease count of the rebroadcast route request (RREQ) packets

RELATED WORK

For route discovery an efficient mechanism is broadcasting, but based on broadcasting there is more overhead on the routing, particularly in the large number of networks. By experimentally and analytically number of researchers deliberated the protocol of broadcasting and observed that the broadcast requires more resources of the network and also it is more expensive. So the more overhead on the routing is placed because of the broadcasting and also causes other problems such as collisions, contentions, and redundant retransmissions [4]. Thus, in route discovery broadcasting optimization is an efficient solution to get better performance of the routing. One of the researcher proposed a approach based on a gossip, in which the packet is forwarded based on the probability. After that it observed that comparing with the flooding mechanism, gossip-based approach decreases overhead on the routing up to thirty five percent, but the gossip-based approach is inadequate when the density of a network is more or at the high traffic load. Some of the researchers explored a probabilistic broadcasting scheme depending on neighbor confirmation and coverage area. This method is to set the probability of rebroadcasting with the help of coverage area and to guarantee reachability it utilizes the neighbor confirmation. Some of the other researchers as per their studies explored a neighbor knowledge scheme known as SBA (Scalable Broadcast Algorithm).

SBA (Scalable Broadcast Algorithm) determines packet rebroadcasting according to the reality this rebroadcast would accomplish the coverage of extra nodes. [7] Projected a DPR (Dynamic Probabilistic Route Discovery) method depending upon the coverage of neighbor information. In this scheme, every node determines the probability of forwarding as per the neighbors count information and the set of neighbors covered based on the earlier broadcast. This method considers the ratio of the coverage by the earlier node only, and it doesn't considered received neighbors Route Request packet (RREQ) is required RREQ packet or duplicate RREQ Packet. Thus, there is a area of additional optimization and expansion for the protocol of DPR. For Broadcasting quite a lot of robust protocols are proposed in the previous year's in addition to the above mentioned optimization issues. [8] explored an AODV-DFR (Adhoc On-demand Distance Vector protocol with Directional Forward Routing) which considers the directional forwarding which is utilized in geographic routing

Volume : 4 | Issue : 7 | July 2015 • ISSN No 2277 - 8179

into Ad hoc On-demand Distance Vector protocol. If the route breakage is occurred for forwarding the packet this protocol automatically searches the next hop node. [9] Explored couple of methods which are based on deterministic timer-based broadcast: DRB (Dynamic Reflector Broadcast) and DCCB (Dynamic Connector-Connector Broadcast). They mentioned that their methods can attain complete reach ability over an unrealistic lossless MAC layer, and their methods are robust in the condition of nodes mobility and node failures. For flooding in wireless networks. [10] explored a RBP (Robust Broadcast Propagation) protocol to present near-perfect reliability and this protocol has a higher efficiency. For broadcasting they gave a new prospective that is a not to create a single broadcast more efficient but to make a single broadcast more reliable, that is to improve the flooding overall performance by decreasing the upper layer frequency appealing to flooding. In our protocol, we also set a deterministic rebroadcast rearrangement, but the aim is to create the broadcasting of neighbor knowledge to a great extent faster

SYSTEM DEVELOPMENT

Rebroadcast rearrangement: The rebroadcast rearrangement is to find out the order of the forwarding packet. If rebroadcast a packet to the node which is having more number of neighbors with the previous node, then that node has the lower delay, so that the more number of common nodes will receive the packet. Rebroadcast rearrangement gives the information that the node has transmitted the packets to more number of neighbor nodes, which is the vital role in the success of the proposed method.

Probability of rebroadcasting: This method has taken the advantage of UCN (uncovered neighbors) information, Connectivity factor, and density of the local node to find the probability of the rebroadcasting. The Probability of the rebroadcasting has two parts

1. Extra Coverage is the ratio between the number of neighbor nodes that needs to be covered by a single broadcast and the total number of nodes.
2. Factor of Connectivity: Connectivity factor gives the relation between the total number of neighbors to the given node and connectivity of the network.

Neighbor coverage-based probabilistic transmit protocol:

In this, we compute the rebroadcast rearrangement and probability of rebroadcasting of the projected protocol. To calculate rebroadcast rearrangement we utilize the received RREQ packet upstream coverage ratio from the last node, and to calculate probability of rebroadcasting we utilize the RREQ packet extra coverage ratio and the factor of connectivity in the above proposed protocol, which needs the information of the 1-hop neighborhood is for each node



Figure 1: Ad hoc On-demand Distance Vector packet delivery ratio

To execute our protocol that was planned we modify AODV source code in NS-2. Observe that the above protocol that was planned needs hello packets to get the neighbor information, and also RREQ packet need to carry the neighbor list information .In this implementation some methods are used to decrease the Hello Packets Overhead and RREQ packet contains the neighbor list which are explained in the below.

To decrease the Hello packets overhead, we are not utilizing periodical Hello packet method. When a node transferring any broadcasting packets can notify its existence of its neighbors, the Route Request (RREQ) and route error (RERR) can play a role of Hello packets in the broadcasting packets. We utilize the below mentioned mechanism [17] to decrease the Hello packets overhead: Node needs to send a Hello Packet only when the elapsed time from the previous broadcasting packet (RREQ, RERR, or many other alternative broadcasting packets) is more than the value of HelloInterval. The value of HelloInterval is similar to that of original AODV

To decrease the neighbor list overhead in the Route Request (RREQ) packet, need to observe every node neighbor table variations and maintain the neighbor list cache in the Route Request (RREQ) packet which was received. We change the AODV RREQ header, and insert a field nn_list that are fixed, here nn_list represents the neighbor list size in the RREQ packet and the nn_list is the neighbor list which is dynamic neighbor list

Maintenance of a Path:

Active routes containing neighboring nodes occasionally swap over hello messages with each other. If another hop link which is next in the routing table not succeeds the active neighbors will get information.

The RERR points towards the destinations which are unreachable.

<source_addr, dest_addr, current sequence# + 1, infinity, lifetime>

The source executes a request of new route when it takes delivery of a RERR. The source executes a request of new route when it takes delivery of a RERR.

Routing Overhead:

Normalized routing load is the number of routing packets transmitted per data packet sent to the destination. Also each forwarded packet is counted as one transmission. Simulation shows difference between AODV Routing Overhead and above proposed routing overhead method with increase in the number of nodes below figure shows the simulation results



Figure 2: Routing Over Head

Packet Delay

Packet delay is the time taken for a packet to be transmitted across a network from source to destination Simulation results shows the difference between AODV Packet delay and proposed packet delay method below figure shows the simulation results



Figure 3: Packet Delay

Packet delivery Ratio:

Packet Delivery ratio is the ratio between the total number of packets received and total number of packets send. Simulation results shows the difference between AODV Packet delivery ratio and proposed packet delivery ratio, below figure shows the simulation results



Figure 4: Packet Delivery Ratio

CONCLUSIONS

In this paper, we have a tendency to explore a protocol of probabilistic rebroadcast that depends upon neighbor coverage to decrease the overhead of routing in MANETs. This neighbor coverage awareness contains extra connectivity factor and ratio of the coverage. We explored a new method to energetically compute the rebroadcast rearrangement, which is utilized to conclude the forwarding manner and more successfully utilize the knowledge of the neighbor coverage. Simulation outputs illustrate that the proposed protocol creates low rebroadcast traffic when it is compared with the flooding and in literatures various other optimized methods. So because of reduced redundant rebroadcast, the protocol alleviates the network contention and collision, so as to increase the ratio of the packet delivery ratio and reduce the average end to end delay. Even when the density of network is high or in heavy load traffic the routing overhead will not be increased.

REFERENCE

[1] D. Johnson, Y. Hu, and D. Maltz, The Dynamic Source Routing Protocol for Mobile Ad Hoc Networks (DSR) for IPv4, IETF RFC 4728, vol. 15, pp. 153-181, 2007. | [2] J.D. Abdulai, M. Ould-Khaoua, and L.M. Mackenzie, "Improving Probabilistic Route Discovery in Mobile Ad Hoc Networks," Proc. IEEE Conf. Local Computer Networks, pp. 739-746, 2007 | [3] X. Wu, H.R. Sadjadpour, and J.J. Garcia-Luna-Aceves, "Routing Overhead as a Function of Node Mobility: Modeling Framework and Implications on Proactive Routing," Proc. IEEE | Int'l Conf. Mobile Ad Hoc and Sensor Systems (MASS '07), pp. 1- 9, 2007. | [4] S.Y. Ni, Y.C. Tseng, Y.S. Chen, and J.P. Sheu, "The Broadcast Storm Problem in a Mobile Ad Hoc Network," Proc. ACM/IEEE MobiCom, pp. 151-162, 1999. | [5] B. Williams and T. Camp, "Comparison of Broadcasting Techniques for Mobile Ad Hoc Networks," Proc. ACM MobiHoc, pp. 194- 205, 2002. | [6] J. Kim, Q. Zhang, and D.P. Agrawal, "Probabilistic Broadcasting Based on Coverage Area and Neighbor Confirmation in Mobile Ad Hoc Networks," Proc. IEEE GlobeCom, 2004. | [7] J.D. Abdulai, M. Ould-Khaoua, L.M. Mackenzie, and A. Mohammed, "Neighbour Coverage: A Dynamic Probabilistic Route Discovery for Mobile Ad Hoc Networks," Proc. Int'l Symp. Performance Evaluation of Computer and Telecomm. Systems (SPECTS '08), pp. 165-172, 2008 | [8] J. Chen, Y.Z. Lee, H. Zhou, M. Gerla, and Y. Shu, "Robust Ad Hoc Routing for Lossy Wireless Environment," Proc. IEEE Conf. Military Comm. (MILCOM '06), pp. 1-7, 2006. | [9] A. Keshavarz-Haddady, V. Ribeirox, and R. Riedi, "DRB and DCCB: Efficient and Robust Dynamic Broadcast for Ad Hoc and Sensor Networks," Proc. IEEE Comm. Soc. Conf. Sensor, Mesh, and Ad Hoc Comm. and Networks (SECON '07), pp. 253-262, 2007. 432 IEEE TRANSACTIONS ON MOBILE COMPUTING, VOL. 12, NO. 3, MARCH 2013 Fig. 11. Packet delivery ratio with varied random packet loss rate. Fig. 12. Average end-to-end delay with varied random packet loss rate. | [10] F. Stann, J. Heidemann, R. Shroff, and M.Z. Murtaza, "RBP: Robust Broadcast Propagation in Wireless Networks," Proc. Int'l Conf. Embedded Networked Sensor Systems (SenSys` '06), pp. 85-98, 2006. |