

GLOBAL RESEARCH ANALYSIS

ISSN No 2277 - 8160

Listed & Indexed with

ISSN Directory, Paris



Multi-Subject Journal

Volume : 1 | Issue : 1 | June 2012 | ₹ 250/-

GLOBAL RESEARCH ANALYSIS

ISSN No 2277 - 8160

GLOBAL RESEARCH ANALYSIS

Editor In-Chief :

Dr. Khansa Memon
SARA Publishing Academy

Dr. Ashok S. Pawar Associate Professor, Dept. of Economic Dr. Babaasaheb Ambedkar Marathwada.University, Aurngabad.(MS-India)-431004	**Dr.(Prof) Vijay Kumar Soni** Principal, Jai Meenesh College, Phagi, Jaipur, Rajasthan	**Dr. A.R. Saravankumar** Assistant Professor in Education DDE, Alagappa University, Tamilnadu
Dr. R. Ramachandran Commerce DDE Annamalai University Tamilna	**Dr. R Ganpathy** Assistant Professor in Commerce Directorate of Distance Education Alagappa University Karaikudi.	**Dr. Amit Bandyopadhyay** Assistant Professor Department of Physiology University of Calcutta
Dr. V. Kumaravel Professor and Head Vivekanandha Business School for Women Tiruchengode, Namakkal Dist	**Dr. K. Prabhakar** Professor, Department of Management Studies, Velammal Engineering College, Chennai - 600 066.	**Dr. Sunita J. Rathod** Maharashtra Education Service Group-B DIET Dist. Jalna

SUBSCRIPTION DETAILS

Period	Rate	Discount	Amount Payable
One Year (12 issues)	3000/-	Nil	3000/-
Two Years (24 issues)	6000/-	200/-	5800/-
Three Years (36 issues)	9000/-	300/-	8700/-
Five Years (60 issues)	15000/-	600/-	14400/-

You can download the Subscription form from website www.theglobaljournals.com. You will require to print the form. Please fill the form completely and send it to the Editor, GLOBAL RESEARCH ANALYSIS along with the payment in the form of Demand Draft/Cheque at Par drawn in favour of GLOBAL RESEARCH ANALYSIS payable at Ahmedabad.

- Thoughts, language, vision and examples in published research paper are entirely of author of research paper. It is not necessary that both the editor, and editorial board agrees with the author. The responsibility of the matter of research paper/article is entirely of author.
- Editing of the Global Research Analysis is processed without any remittance. The selection and publication is done after recommendations of atleast two subject expert referees.
- In any condition if any National/International University denies accepting the research paper published in GRA, then it is not the responsibility of Editor, Publisher and Management
- Only the first author is entitle to receive the copies of all co-authors
- Before re-use of published paper in any manner, it is compulsory to take written permission from the Editor-GRA unless it will be assumed as disobedience of copyright rules
- All the legal undertaking related to Global Research Analysis is subject to Ahmedabad Jurisdiction.
- The research journal will be send by normal post. If the journal is not received by the author of research paper then it will not be the responsibility of the Editor and publisher. The amount for registered post should be borne by author of the research paper in case of second copy of the journal.

Editor,
GLOBAL RESEARCH ANALYSIS
3, SUHANA, Near. Ruby Apartment, B/h NID, Rajnagar Road, Paldi Ahmedabad – 380007. Gujarat (INDIA)
Cell : +91 98247 02127, 8866 00 3636

INDEX

Sr. No.	Title	Author	Subject	Page No.
1	Vat And Accounting and Emerging Financial Services	Dr.Kishor V. Bhesaniya	Accountancy	1-2
2	Regulations for Alternative Investment Funds – A Primer	Dr. Bheemanagouda	Commerce	3-4
3	Financial Inclusion in India: A Real Effort for Growth	Dr. Jyotindra M. Jani, Manish B. Raval	Commerce	5-6
4	Tourism Industry and Medical Tourism in India – An Analysis	Dr. M. K. Maru	Commerce	7-8
5	Enhancing Supply Chain Performance through Effective Transportation	Dr. Vipul Chalotra	Commerce	9-10
6	Growth of Consumer Co-Operatives in J&K- A Study	Tarsem Lal	Commerce	11-12
7	Uses of College Funds in Assam-With Reference to Lakhimpur District	Dr. Niranjan Kakati	Commerce	13-14
8	LIC –A Modle Employer	Dr.J.K.Sehgal	Commerce	15-16
9	A study of the use of Information technology enabled banking services by Indian Customers	Dr Sunny Thomas, MsWaheeda Sheikh	Economics	17-18
10	The Role of Women Entrepreneurs in The Emerging Economic Force	Dr.Sangappa.V. Mamanshetty	Economics	19-21
11	Trade-off Between Inflation and Unemployment for BRICS Countries – Dead or Alive?	Krunal K Bhuva, Ashok R. Bantwa	Economics	22-23
12	Urbanisation and its Impact on Poverty	Dr. K.J. Thankachan, Mrs. Nazia Ansari	Economics	24-25
13	Food Security- Issues and Concerns	Munisha Gaur	Economics	26-27
14	Teaching Strategies : A Model Approach	Dr. Mujibul Hasan Siddiqui	Education	28-29
15	School Curriculum in Terms of Life Skills and its Implications for Teacher Education	Ramesh B. Sakhiya	Education	30-31
16	Edge Detection using live video acquisition	Patel Janakkumar Baldevbhai, R.S. Anand, Patel Nilam J.	Engineering	32-34
17	Topological Characteristics of Dynamics of Heart in Various Pathological Cases using Lyapunov Exponent and RBF Network	Abinash Dahal, Deepashree Devaraj, Dr. N. Pradhan	Engineering	35-37
18	Implementation of Digital Logic Method for Selection of Material of Automotive Brake Disc	Mr. Keval J. patel, Tushar M. Patel, Ankit A. Darji	Engineering	38-40
19	Initial and after Market Performance of Indian IPOs	Dr. Ashvin H. Solanki	Finance	41-43
20	Facilitation of Collateral Free Loan to Improve Financial Linkages For Start Up & Growth – A Case Study	D M Parikh	Finance	44-46
21	Impact of Maternal Nutrition Education Module on Nutritional Knowledge And Status in Rural Pregnant Women	Dr. Anjali A. Rajwade	Home Science	47-49
22	Trends and Challenges in Indian Insurance Industry	Dr Mahalaxmi Krishnan	Insurance	50-51
23	(Raksha Patrakarita : Dayra Badhae Media Sansthan)	Dr. Subodh Kumar	Journalism	52-53
24	NATIONAL WAGE POLICY VIZ-A-VIZ CORRELATION BETWEEN WAGES, PRICE AND TAX	Manish Parshuram Pawar, Dr. Ashok Shankarrao Pawar	Law	54-55

Sr. No.	Title	Author	Subject	Page No.
25	Shobha De's treatment of sex in Starry Nights	Chetan J. Marakana	Literature	56
26	A Catalyst to Promote Teaching and Learning English Grammar	Elsamma Sebastian	Literature	57-58
27	A Study on Effectiveness of Employee Training in Health Care Industry in a Private Multi-Speciality Organization	Dr C Swarnalatha, TS Prasanna	Management	59-61
28	Insights in to the Tomorrow Retailing in India: A Point of View and Method	Anuradha Averineni	Management	62-63
29	A Study on the Excellence of Worklife Among the Employees of it Sector in Coimbatore	G. Murali Manokari, R.Kanaka Rathinam	Management	64-65
30	Socio Cultural Issues in Marketing	Kavita A. Trivedi	Management	66-67
31	Organised Multi Brand Retailing: Opportunity For Sustainable Development	Rachita Sambyal	Management	68-69
32	Investors Perception for Mutual Fund Investment in 21st Century	Dr. Deepak H. Tekwani	Management	70-71
33	FDI in India	Dr. M Venkata Subba Reddy, Mr.udaya Banu	Management	72-73
34	Global Crisis and Indian Economy, A Comparative Analysis with World Economy	Dr. Pankaj K. Trivedi	Management	74-76
35	Practical Utility of Intellectual Capital Approach-A Critical Analysis	Dr. Shilpa Trivedi	Management	77-78
36	An In-depth study of Consumer Preference towards Personal Care Products	Dr.Sharif Memon	Management	79-81
37	Consumer Awareness and Preferences towards Ayurvedic Cosmetic Products in Coimbatore City	Mrs. B. Menaka, Dr. T. Ramasamy, Dr. R. Ganapathi	Management	82-90
38	Miracle combination of five herbs Methi, Kalongi, saunf, jeera and Rai	Dr. Sneh Harshendra Sharma	Management	91-93
39	Social Marketing: Towards a new horizon	Dr Partha Sarkar	Marketing	94-95
40	Epidemiological Transition and Emerging Conflicts in Health Care	Dr. Pawan Kumar, Dr. Abdul Majeed Khan	Public Health	96-97
41	Knowledge, Attitude and Practice of Reproductive Health Care Services among the Members and Non-members of Self Help Groups (SHGs)	Dr.K.Jothy	Social Sciences	98-100

Volume : 1 | Issue : 1 | June 2012 • ISSN No 2277 - 8160

Research Paper | Engineering

Implementation of Digital Logic Method for Selection of Material of Automotive Brake Disc

Mr. Keval J. patel PG student, ME Production Engg., L.D.R.P-I.T.R, Gandhingar

Tushar M. Patel Asst. Prof., Mech. Engg. Dept., L.D.R.P-I.T.R, Gandhingar

Ankit A. Darji Asst. Prof., Mech. Engg. Dept., L.D.R.P-I.T.R, Gandhingar

ABSTRACT

An automotive brake disc or rotor is a device for slowing or stopping the motion of a wheel while it runs at a certain speed. The widely used brake rotor material is cast iron which consumes much fuel due to its high specific gravity. The aim of this paper is to develop the material selection method and select the optimum material for the application of brake disc system emphasizing on the substitution of this cast iron by any other lightweight material. Two methods are introduced for the selection of materials, such as cost per unit property and digital logic methods. Material performance requirements were analyzed and alternative solutions were evaluated among cast iron, aluminium alloy, titanium alloy, ceramics and composites. Mechanical properties including compressive strength, friction coefficient, wear resistance, thermal conductivity and specific gravity as well as cost, were used as the key parameters in the material selection stages. The analysis led to aluminium metal matrix composite as the most appropriate material for brake disc system. Index Terms— Brake disc; Material selection; Cost per unit strength method; Digital logic method.

KEYWORDS: Composites, Automobile Disc Brake, Digital Logic Method, Material Selection

1. Introduction

In automotive industries, to achieve reduced fuel consumption as well as green house gas emission is a current issue of utmost importance. To reduce automobile weight and improve fuel efficiency, the auto industry has dramatically increased the use of aluminum in light vehicles in recent years. Aluminum alloy based metal matrix composites (MMCs) with ceramic particulate reinforcement have shown great promise for such applications [1, 2]. These materials having a lower density and higher thermal conductivity as compared to the conventionally used gray cast irons are expected to result in weight reduction of up to 50 – 60 % in brake systems [3]. There are several factors to be considered when selecting a brake disc material. The most important consideration is the ability of the brake disc material to withstand high friction and less abrasive wear. Another requirement is to withstand the high temperature that evolved due to friction. In general, the material selection process is performed based on performance indices in chart [5]. As an alternative approach, digital logic methods have been occasionally used in material selection for certain engineering application [6]. The information on the development and application of the materials selection method for the design of automotive brake disc is scare in literature. The main purpose of the present work is to develop a suitable material selection method and apply that for the selection of best candidate material for brake disc application using Ashby's chart and finally rank the materials according to the performance indices using digital logic method.

II. STAGE OF MATERIAL SELECTION

For material selection there are small numbers of methods that have evolved to a position of prominence [9]. Material selection process is an open-ended and normally lead to several possible solutions to the same problem. This can be illustrated by the fact that similar component performing similar function, but produced by different manufacturers, are often made from different materials and even by different manufacturing processes [10]. However, selecting the optimum combination of material and process is not a simple task rather gradually evolved processes during the different stages of material selection. In this investigation, the stages of material selection method are shown using a flow chart in Figure.1.

General material performance requirements
⇩
Initial screening of candidate material
⇩
Material selection using Digital Logic Method
⇩
Optimum material selection

Figure.1 Flow chart of material selection method

III. GENERAL MATERIAL PERFORMANCE REQUIREMENTS

Disc brake systems generate braking force by clamping brake pads onto a rotor that is mounted to the hub. A schematic view of the brake system is shown in Fig.2.The higher the coefficient of friction for the pad, the more brake power will be generated. Coefficient of friction can vary depending on the type of material used for the brake rotor. Typically service brakes are concerned with dynamic coefficient of friction, or the coefficient of friction measured while the vehicle is moving.

$$F_{rotor} = 2C_{f,pad} F_{pad} \quad (1)$$




Figure.2 Schematic view of real size brake system

(brake disc and brake pad)

IV. INITIAL SCREENING OF CANDIDATE MATERIAL

Traditional material for automotive brake rotor is the cast iron. The specific gravity or density of cast iron is higher which consumes much fuel due to high inertia. Following section will describe the potential candidate materials those can be used for brake rotor application.

Cast Iron: Metallic iron containing more than 2% dissolved carbon within its matrix (as opposed to steel which contains less than 2%) but less than 4.5% is referred to as gray cast iron because of its characteristic colour. Considering its cost, relative ease of manufacture and thermal stability, this cast iron (particularly, gray cast iron), is actually a more specialized material for brake applications particularly the material of choice for almost all automotive brake discs. [12].

Titanium alloys: Titanium alloys and their composites have the potential to reduce weight of the brake rotor disc component which is about 37% less than a conventional cast iron with the same dimensions and offering good high temperature strength and better resistance to corrosion [13].

Aluminum-Metal Matrix Composite (AMC):
Aluminum alloy based metal matrix composites (MMCs) with ceramic particulate reinforcement have shown great promise for brake rotor applications. These materials having a lower density and higher thermal conductivity as compared to the conventionally used gray cast irons are expected to result in weight reduction of up to 50-60% in brake systems.

Based on the properties, potential candidate materials for automotive brake disc were selected as:

- Gray cast iron (GCI)
- Ti-alloy (Ti-6Al-4V)
- 7.5 wt% WC and 7.5 wt% TiC reinforced Ti-composite (TMC)
- 20% SiC reinforced Al-composite (AMC 1)
- 20% SiC reinforced Al-Cu alloy (AMC2)

V. material selection using digital logic method

The digital logic method can be employed for the optimum material selection using with ranking. As a first step, the property requirements for a brake rotor were determined based on previous discussion. The properties and the total number of decisions, i.e. N (N – 1)/2 = 10, are given in Table 1. The weighting factor for each property, which is indicative of the importance of one property as compared to others, was obtained by dividing the numbers of positive decisions given to each property by the total number of decisions. The total positive decisions for each property and corresponding weighting factor were calculated and are presented in Table 2. From Table 2, it can be seen that friction coefficient and wear resistance have the highest weighting factors followed by thermal capacity, whereas the least important properties are compressive strength and specific gravity hence, obtained lower weighting factor.

Table.1 Application of digital logic method to material selection for brake disc

Decision Numbers										
	1	2	3	4	5	6	7	8	9	10
Compressive Strength	0	0	0	1						
Friction coefficient	1				1	0	1			
Wear resistance		1			0			1	1	
Thermal capacity			1			1		0		0
Specific gravity				0			0		0	1

Table.2 Weighting factors for brake disc

Property	Positive decisions	Weighting factors
Compressive Strength	1	0.1
Friction coefficient	3	0.3
Wear resistance	3	0.3
Thermal capacity	2	0.2
Specific gravity	1	0.1
Total	10	1.0

Table 3 showed the properties of the candidate materials those are used for ranking purposes. In order to complete the DL method, the next step is to scale the properties of the materials based on their respective weighting factor and the scale value is shown in Table 3. For the present application, materials with higher compressive strength, friction coefficient and thermal capacity are more desirable and highest value is rated as 100. Their scaled values are calculated using the following equation (2).

$$\text{scaled property} = \frac{\text{numerical value of property}}{\text{maximum value in the li}} \quad (2)$$

Since lower wear rate and specific gravity are desirable for the automotive brake disc, therefore, their lowest value is considered as 100 and scaled values are calculated using equation (3).

$$\text{scaled property} = \frac{\text{numerical value of prope}}{\text{numerical value of the p}} \quad (3)$$

Other values in Table 4 are rated in proportion. The scaled values and performance index (γ) are given in Table 5 which was calculated using equations (4) [10].

Material performance index, $\gamma = \sum_{i=1}^{n} \beta i \alpha i$ (4)

Where β is the scaled property, α is the weighting factor and i is summed over all the n relevant properties.

Table.3 Properties of candidate materials for brake disc [11, 13]

Property / Material	1 Compressive strength (MPa)	2 Friction coefficient (μ)	3 Wear rate ($\times 10^{-6}$ $mm^3/N/m$)	4 Specific heat (KJ/ Kg K)	5 Specific gravity (Mg/m^3)
GCI	1293	0.41	2.36	0.46	7.2
Ti-6Al-4V	1070	0.34	246.3	0.58	4.42
TMC	1300	0.31	8.19	0.51	4.68
AMC 1	406	0.35	3.25	0.98	2.7
AMC 2	761	0.44	2.91	0.92	2.8

Table.4 Scaled value of properties of each material and corresponding performance index

Scaled properties						
	1	2	3	4	5	Performance Index (γ)
GCI	99	93	100	47	38	81.0
Ti-6Al-4V	82	77	0.96	59	61	49.5
TMC	100	70	29	52	58	56.0
AMC 1	31	80	73	100	100	79.0
AMC 2	59	100	81	94	96	88.6

The performance index showed that the technical capability of the material without regard to the cost. However, if there are a large number of properties to be considered, the importance of cost may be emphasized by considering it separately as a modifier to the material performance index (γ). It is also important to consider the cost of material before making any final design or ranking. Therefore, in this study, the figure of merit (FOM) M is calculated before ranking using the equation (5):

$$M = \frac{\gamma}{C\rho} \quad (5)$$

Where,
C=Total cost of the material per unit weight
ρ = Density of the material

Table. 5 Cost and figure of merit of candidate materials

Material	Relative cost	Performance index	Figure of merit	Rank
GCI	1	81.0	11.25	2
Ti-6Al-4V	20	49.5	0.56	5
TMC	20.5	56.0	0.58	4
AMC 1	2.7	79.0	10.84	3
AMC 2	2.6	88.6	12.17	1

The values of the relative cost, performance index, and figure of merits of the different materials are shown in Table 5. The plot of performance indices against all the candidate materials is shown in Fig. 3. From Fig. 3 it can be seen that AMC 2 (Al-Cu alloy reinforced with 20% SiC) showed higher performance index (γ) followed by gray cast iron (GCI) material.




Figure.3 Plot of performance index (γ) against all candidate materials.

VI. OPTIMUM MATERIAL SELECTION

In this section, the performance index, γ, and the total cost, Ct of the candidate material AMC 2 are separately compared against the currently used gray cast iron (GCI). Since the purpose is to improve performance, acceptable candidates must perform at a higher level than the currently used material. If cost is not the objective, the candidate with the highest performance index, γ, can be selected. The percentage increase in performance (Δγ %) and the corresponding percentage increase in cost (Δ Ct %) for both the candidate materials and the currently used material is calculated using equation (6) and (7) respectively and values are summarized in Table 6.

$$\Delta\gamma\% = \frac{100(\gamma_n - \gamma_0)}{\gamma_0} \quad \ldots\ldots (6)$$

$$\Delta C_t\% = \frac{100(C_{tn} - C_{t0})}{C_{t0}} \quad \ldots\ldots (7)$$

Where,
γn and γ0 = performance indices of the new and original materials,
Ctn and Ct0 = cost of the new and original materials, respectively.

Table. 6 The percentage increase in performance (Δγ %) and the corresponding percentage increase in cost (Δ Ct %) for both the candidate materials

Material	Performance index(γ)	Total cost (£/ton) Ct	Δγ %	ΔC_t %
GCI	81.0	830	9.4	167.5
AMC 2	88.6	2220		

VII. CONCLUSION

The material selection methods for the design and application of automotive brake disc are developed. Functions properties of the brake discs or rotors were considered for the initial screening of the candidate materials using Ashby's materials selection chart. The digital logic method showed the highest performance index for AMC 2 material and identified as an optimum material among the candidate materials for brake disc. In the digital logic method, the friction coefficient and density were considered twice for determining the performance index and the cost of unit property. This procedure could have overemphasized their effects on the final selection. This could be justifiable in this case as higher friction coefficient and lower density are advantageous from the technical and economical point of view for this type of application.

REFERENCES

[1] R.M. Wang And M.K. Surappa, Microstructure And Interface Structure Studies Of Sicp-Reinforced Al (6061) Metal-Matrix Composites Materials Science And Engineering. A, 254 (1-2), (1998), 219-226. | [2] Shaoyang Zhang, Fuping Wang, Comparison Of Friction And Wear Performances Of Brake Material Dry Sliding Against Two Aluminium Matrix Composites Reinforced With Different Sic Particles, Journal Of Materials Processing Technology 182 (2007) 122–127. | [3] T.F. Stephenson Et Al., Aluminium Hybrid Composites Containing Nickel-Coated Graphite Particulate, Processing, Properties And Applications Of Cast Metal Matrix Composites, Eds. P. Rohatgi And P.A. Khan (Warrendale, PA: TMS, 1996), Pp. 337–351. | [4] Ashby M F. Materials Selection In Mechanical Design.3rd Ed. UK: Butterworth Heinemann; 2005. | [5] Shanian A, Milani A S, Carson C, Abeyaratne R C. A New Application Of ELECTRE III And Revised Simos' Procedure For Group Material Selection Under Weighting Uncertainty. Knowledge-Based Systems 21 (2008) 709–720. | [6] Jahazi M, Hossein-Nejad S. The Development Of An Optimum Manufacturing And Material Selection Process For The Fabrication Of Labyrinth Seal Strips, Journal Of Materials Processing Technology 152 (2004), 272–275. | [7] Sapuan, S. M. Jacob, M. S. D. Mustapha, F. Ismail, N. A Prototype Knowledge-Based System For Material Selection Of Ceramic Matrix Composites Of Automotive Engine Components, Materials & Design, Volume 23, Issue 8, (2002)701-708. | [8] Zhu, F., Lu, G., Zou, R. On The Development Of A Knowledge-Based Design Support System For Energy Absorber, Materials & Design, Volume 29, Issue 2, (2008), 484-491. | [9] Dieter G E, Engineering Design. 3rd Ed. USA: Mcgraw-Hill; 2000. | [10]Farag M M. Materials And Process Selection For Engineering Design. 2nd Ed. New York: CRC Press; 2008, P. 259-280. | [11] Www.Hayesdiscbrake.Com/Hayesu_Product1.S.Html | [12] G. Cueva, A. Sinatora, W.L. Guesser And A.P. Tschiptschin, Wear Resistance Of Cast Irons Used In Brake Disc, Wear 255 (2003), 1256-1260. | [13] M.A. Maleque[1], S.Dyuti2 and M.M. Rahman, Material Selection Method in Design of Automotive Brake Disc, Proceedings of the World Congress on Engineering 2010 Vol III WCE 2010, July, 2010 | [14] S. Wilson And A. Ball, Tribology Of Composite Materials, In: P.K. Rohatgi, P.J. Blau, C.S. Yust (EDS.), Conference Proceedings Oak Ridge. ASM International, Materials Park. OH, May 1-3, 1990, P1-14. | [15] G.J. Howell, A. Ball, Dry Sliding Wear Of Particulate-Reinforced Aluminium Alloys Against Automobile Friction Materials, Wear 181-183 (1995), 379-390. | [16] Peter J. Blau, Brian C. Jolly, Jun Qu, William H. Peter, Craig A. Blue. Tribological Investigation of Titanium-Based Materials for Brakes, Wear 263 (2007), 1202–1211.



Sara Publishing Academy

GLOBAL RESEARCH ANALYSIS

Multi-Subject Journal

Editor,

GLOBAL RESEARCH ANALYSIS

3, SUHANA, Nr. Ruby Apartment,
B/h NID, Rajnagar Circle, Paldi, Ahmedabad - 380007

Printed at Unique Offset, Novatsing Rupam Estate, Opp. Abhay Estate, Tavdipura, Shahibaug, Ahmedabad

Designed By : Advocate, +91 9824811412