

Research Paper

Computer Science

E-Waste Management

S.Kanagarathinam

Assistant Professor, Department Of Computer Science, PSGR Krishnammal College for Women, Coimbatore

S.kiruthika Devi

Assistant Professor, Department Of Computer Science, PSGR Krishnammal College for Women, Coimbatore

ABSTRACT

Electronic waste or e-waste is a popular, informal name for electronic products nearing the end of their "useful life.
E-waste comprises of a multitude of components, some containing toxic substances that can have an adverse impact
he environment if not handled properly. The hazardous content of these materials pose a threat to human health and

on human health and the environment if not handled properly. The hazardous content of these materials pose a threat to human health and environment. Discarded computers, televisions, VCRs, stereos, copiers, fax machines, electric lamps, cell phones, audio equipment and batteries if improperly disposed can leach lead and other substances into soil and groundwater. Many of these products can be reused, refurbished, or recycled in an environmentally sound manner so that they are less harmful to the ecosystem.

This paper highlights the hazards of e-wastes, the need for its appropriate management and options that can be implemented.

KEYWORDS:

INTRODUCTION

Industrial revolution followed by the advances in information technology during the last century has radically changed people's lifestyle. Although this development has helped the human race, mismanagement has led to new problems of contamination and pollution. The technical prowess acquired during the last century has posed a new challenge in the management of wastes. For example, personal computers (PCs) contain certain components, which are highly toxic, such as chlorinated and brominated substances, toxic gases, toxic metals, biologically active materials, acids, plastics and plastic additives. The hazardous content of these materials pose an environmental and health threat. Thus proper management is necessary while disposing or recycling e wastes.

These days computer has become most common and widely used gadget in all kinds of activities ranging from schools, residences, offices to manufacturing industries. E-toxic components in computers could be summarized as circuit boards containing heavy metals like lead & cadmium; batteries containing cadmium; cathode ray tubes with lead oxide & barium; brominated flame retardants used on printed circuit boards, cables and plastic casing; poly vinyl chloride (PVe) coated copper cables and plastic computer; casings that release highly toxic dioxins & furans when burnt to recover valuable metals; mercury switches; mercury in flat screens; poly chlorinated biphenyl's (PCB's) present in older capacitors; transformers; etc. Basel, Action Network (BAN) estimates that the 500 million computers in the world contain 2.87 billion kgs of plastics, 716.7 million kgs of lead and 286,700 kgs of mercury. The average 14-inch monitor uses a tube that contains an estimated 2.5 to 4 kgs of lead. The lead can seep into the ground water from landfills thereby contaminating it. If the tube is crushed and burned, it emits toxic fumes into the air.

EFFECTS ON ENVIRONMENT AND HUMAN HEALTH

Disposal of e-wastes is a particular problem faced in many regions across the globe. Computer wastes that are landfilled produces contaminated leachates which eventually pollute the groundwater. Acids and sludge obtained from melting computer chips, if disposed on the ground causes acidification of soil. For example, Guiyu, Hong Kong a thriving area of illegal e-waste recycling is facing acute water shortages due to the contamination of water resources.

This is due to disposal of recycling wastes such as acids, sludges etc. in rivers. Now water is being transported from faraway towns to cater to the demands of the population. Incineration of e-wastes can emit toxic fumes and gases, thereby polluting the surrounding air. Improperly monitored landfills can cause environmental hazards. Mercury will leach when certain electronic devices, such as circuit breakers are destroyed. The same is true for polychlorinated biphenyls (PCBs) from condensers. When brominated flame retardant plastic or cadmium containing plastics are landfilled, both polybrominated dlphenyl ethers

(PBDE) and cadmium may leach into the soil and groundwater. It has been found that significant amounts of lead ion are dissolved from broken lead containing glass, such as the cone glass of cathode ray tubes, gets mixed with acid waters and are a common occurrence in landfills.

Not only does the leaching of mercury poses specific problems, the vaporization of metallic mercury and dimethylene mercury, both part of Waste Electrical and Electronic Equipment (WEEE) is also of concern. In addition, uncontrolled fires may arise at landfills and this could be a frequent occurrence in many countries. When exposed to fire, metals and other chemical substances, such as the extremely toxic dioxins and furans (TCDD tetrachloro dibenzo-dioxin, PCDDs-polychlorinated dibenzodioxins. PBDDs-poly brominated dibenzo-dioxin and PCDFspoly chlorinated dibenzo furans) from halogenated flame retardant products and PCB containing condensers can be emitted. The most dangerous form of burning e-waste is the open-air burning of plastics in order to recover copper and other metals. The toxic fall-out from open air burning affects both the local environment and broader global air currents, depositing highly toxic byproducts in many places throughout the world.

MANAGEMENT OF E-WASTES

It is estimated that 75% of electronic items are stored due to uncertainty of how to manage it. These electronic junks lie unattended in houses, offices, warehouses etc. and normally mixed with household wastes, which are finally disposed off at landfills. This necessitates implementable management measures. In industries management of e-waste should begin at the point of generation. This can be done by waste minimization techniques and by sustainable product design. Waste minimization in industries involves adopting:

- · inventory management,
- production-process modification,
- volume reduction,
- Recovery and reuse.

Inventory management

Proper control over the materials used in the manufacturing process is an important way to reduce waste generation (Freeman, 1989). By reducing both the quantity of hazardous materials used in the process and the amount of excess raw materials in stock, the quantity of waste generated can be reduced. This can be done in two ways i.e. establishing material-purchase review and control procedures and inventory tracking system.

Developing review procedures for all material purchased is the first step in establishing an inventory management program. Procedures should require that all materials be approved prior to purchase. In the approval process all production materials are evaluated to examine if they contain hazardous constituents and whether alternative non-hazardous materials are available.

Another inventory management procedure for waste reduction is to ensure that only the needed quantity of a material is ordered. This will require the establishment of a strict inventory tracking system. Purchase procedures must be implemented which ensure that materials are ordered only on an as-needed basis and that only the amount needed for a specific period of time is ordered.

Production-process modification

Changes can be made in the production process, which will reduce waste generation. This reduction can be accomplished by changing the materials used to make the product or by the more efficient use of input materials in the production process or both. Potential waste minimization techniques can be broken down into three categories:

- i) Improved operating and maintenance procedures,
- ii) Material change and
- iii)Process-equipment modification.

Improvements in the operation and maintenance of process equipment can result in significant waste reduction. This can be accomplished by reviewing current operational procedures or lack of procedures and examination of the production process for ways to improve its efficiency. Instituting standard operation procedures can optimize the use of raw materials in the production process and reduce the potential for materials to be lost through leaks and spills. A strict maintenance program, which stresse corrective maintenance, can reduce waste generation caused by equipment failure. An employee-training program is a key element of any waste reduction program. Training should include correct operating and handling procedures, proper equipment use, recommended maintenance and inspection schedules, correct process control specifications and proper management of waste materials.

Hazardous materials used in either a product formulation or a production process may be replaced with a less hazardous or non-hazardous material. This is a very widely used technique and is applicable to most manufacturing processes. Implementation of this waste reduction technique may require only some minor process adjustments or it may require extensive new process equipment. For example, a circuit board manufacturer can replace solvent-based product with water-based flux and simultaneously replace solventvapor degreaser with detergent parts washer.

Installing more efficient process equipment or modifying existing equipment to take advantage of better production techniques can significantly reduce waste generation. New or updated equipment can use process materials more efficiently producing less waste. Additionally such efficiency reduces the number of rejected or off-specification products, thereby reducing the amount of material which has to be reworked or disposed of. Modifying existing process equipment can be a very cost-effective method of reducing waste generation. In many cases the modification can just be relatively simple changes in the way the materials are handled within the process to ensure that they are not wasted. For example, in many electronic manufacturing operations, which involve coating a product, such as electroplating or painting, chemicals are used to strip off coating from rejected products so that they can be recoated. These chemicals, which can include acids, caustics, cyanides etc are often a hazardous waste and must be properly managed. By reducing the number of parts that have to be reworked, the quantity of waste can be significantly reduced.

Volume reduction

Volume reduction includes those techniques that remove the hazardous portion of a waste from a non-hazardous portion. These techniques are usually to reduce the volume, and thus the cost of disposing of a waste material. The techniques that can be used to reduce wastestream volume can be divided into 2 general categories: source segregation and waste concentration. Segregation of wastes is in many cases a simple and economical technique for waste reduction. Wastes containing different types of metals can be treated separately so that the metal value in the sludge can be recovered. Concentration of a waste stream may increase the likelihood that the material can be recycled or reused. Methods include gravity and vacuum filtration, ultra filtration, reverse osmosis, freeze vaporization etc.

Recovery and reuse

This technique could eliminate waste disposal costs, reduce raw material costs and provide income from a salable waste. Waste can be recovered on-site, or at an off-site recovery facility, or through inter industry exchange. A number of physical and chemical techniques are available to reclaim a waste material such as reverse osmosis, electrolysis, condensation, electrolytic recovery, filtration, centrifugation etc. For example, a printed-circuit board manufacturer can use electrolytic recovery to reclaim metals from copper and tin-lead plating bath.

However recycling of hazardous products has little environmental benefit if it simply moves the hazards into secondary products that eventually have to be disposed of. Unless the goal is to redesign the product to use nonhazardous materials, such recycling is a false solution

Sustainable product design

Minimization of hazardous wastes should be at product design stage itself keeping in mind the following factors.

- Rethink the product design: Efforts should be made to design a product with fewer amounts of hazardous materials. For example, the efforts to reduce material use are reflected in some new computer designs that are flatter, lighter and more integrated. Other companies propose centralized networks similar to the telephone system.
- Use of renewable materials and energy: Bio-based plastics are plastics made with plant-based chemicals or plantproduced polymers rather than from petrochemicals. Bio-based toners, glues and inks are used more frequently. Solar computers also exist but they are currently very expensive.
- Use of non-renewable materials that are safer: Because
 many of the materials used are non-renewable, designers could
 ensure the product is built for re-use, repair and/or upgradeability. Some computer manufacturers such as Dell and Gateway lease
 out their products thereby ensuring they get them back to further
 upgrade and lease out again

Responsibility and Role of industries

- Generator of wastes should take responsibility to determine the output characteristics of wastes and if hazardous, should provide management options.
- All personnel involved in handling e-waste in industries including those at the policy, management, control and operational levels, should be properly qualified and trained. Some are given below:
- Use label materials to assist in recycling (particularly plastics).
- Standardize components for easy disassembly.
- Re-evaluate 'cheap products' use, make product cycle 'cheap' and so that it has no inherent value that would encourage a recycling infrastructure.
- Create computer components and peripherals of biodegradable materials.
- Utilize technology sharing particularly for manufacturing and de manufacturing.
- Encourage / promote / require green procurement for corporate
- Look at green packaging options.
- 3. Companies can and should adopt waste minimization techniques, which will make a significant reduction in the quantity of e-waste generated and thereby lessening the impact on the environment. It is a "reverse production" system that designs infrastructure to recover and reuse every material contained within e-wastes metals such as lead, copper, aluminum and gold, and various plastics, glass and wire. Such a "closed loop" manufacturing and recovery system offers a win-win situation for everyone, less of the Earth will be mined for raw materials, and groundwater will be protected, researchers explain.
- Manufacturers, distributors, and retailers should undertake the responsibility of recycling/disposal of their own products.
- Manufacturers of computer monitors, television sets and other electronic devices containing hazardous materials must be responsible for educating consumers and the general public regarding the potential threat to public health and the environment posed by their products. At minimum, all computer monitors, television sets and other electronic devices containing hazardous ma-

terials must be clearly labeled to identify environmental hazards and proper materials management.

Responsibilities of the Citizen

Waste prevention is perhaps more preferred to any other waste management option including recycling. Donating electronics for reuse extends the lives of valuable products and keeps them out of the waste management system for a longer time. But care should be taken while donating such items i.e. the items should be in working condition.

Reuse, in addition to being an environmentally preferable alternative, also benefits society. By donating used electronics, schools, non-profit organizations, and lower-income families can afford to use equipment that they otherwise could not afford.

E-wastes should never be disposed with garbage and other household wastes. This should be segregated at the site and sold or donated to various organizations.

While buying electronic products opt for those that:

- are made with fewer toxic constituents
- use recycled content
- are energy efficient
- are designed for easy upgrading or disassembly

- utilize minimal packaging
- offer leasing or take back options
- have been certified by regulatory authorities. Customers should opt for upgrading their computers or other electronic items to the latest versions rather than buying new equipments.

CONCLUSION

Green it is extremely popular. It is not only seen as an organizational responsibility but is also the responsibility that must be undertaken by all computer users. Home computer owners must also resort to green computing practices to make the environment more sustainable. E-waste management plays a vital role in contributing towards green IT .improperly managed it is hazardous to the environment. India is placed in a very interesting position. The need of the hour is an urgent approach to the e-waste hazard by technical and policy-level interventions, implementation and capacity building and increase in public awareness such that it can convert this challenge into an opportunity to show the world that India is ready to deal with future problems

REFERENCES

Third World Network, Malaysia.

1. Ramesh Babu B, Parande AK, Ahmed Basha C. Electrical and electronic waste: A global environmental problem. Waste Manag Res. 2007;25:307–18. [PubMed] | 2. Sinha S. Downside of the Digital Revolution. Published in Toxics Link, 28/12/2007. Available from:http://www. toxicslink.org/art-view.php?id=124. [last accessed on 2008 Jan 1] | 3. Swerts T. Waste or opportunity? - The importance of a progressive Indian e-waste policy. Published in Toxics Link 17/11/2006. Available from: http://www.toxicslink.org/art-view.php?id=116. [last accessed on 2008 Jan 1] | 4.Freeman M. H. 1989. Standard Handbook of Hazardous Waste Treatment and Disposal, McGraw-Hill Company, USA. | 5. Third World Network. 1991. Toxic Terror: Dumping of Hazardous Wastes in the Third World,

GJRA - GLOBAL JOURNAL FOR RESEARCH ANALYSIS № 21