

Fuzzy Sequencing Problem



Mathematics

KEYWORDS : Fuzzy sequencing problem, triangular fuzzy numbers, fuzzy arithmetic and ranking functions.

K.Kripa

Assistant Professor, St.Thomas college of Arts and Science, Chennai, India

R.Govindarajan

Professor and Head, D G Vaishnav College, Chennai , India

ABSTRACT

In this paper, we present the different methods to solve fuzzy sequencing problem using fuzzy technological values like triangular fuzzy numbers. In addition, as a special case, a numerical example is illustrated where non-negative fuzzy values were not used. The procedure adopted was the fuzzy sequencing problems are defuzzified using ranking functions and hence solving the crisp sequencing problem by standard sequencing algorithm for obtaining the optimal sequence and minimum completion time in terms of fuzzy values which is illustrated with numerical examples and solutions.

1.0.Introduction

Operations research is a problem solving and decision making Science. Modeling is the essence of operations research. Formulating a model help us to convert the complexities and uncertainties of a decision making problem to a logical model which is open to formal analysis. It also involves the application of scientific tools for finding optimum solution to the problem involving the operations of system.

A sequencing problem is to determine the optimal sequence in which 'n' jobs to be performed by 'm' machine and various optimality criteria like minimum elapsed time , minimum idle time , minimum inventory cost with the given conditions i) the order of the machine in which each job should be performed ii) the actual or expected time required by the jobs on each of the machine.

Sequencing have been most commonly encountered in production shops where different products are to be processed over various combinations of machines.

The complicated real life situations are defined in terms of impressions which was overcame by **Zadeh** with a powerful tool of fuzzy data. Thus fuzzy sequencing problem plays a vital role in formulating the uncertainty in actual environment.

This paper is framed as follows section2:Basic definitions and preliminary results, section 3:Application of ranking functions to solve Fuzzy sequencing problem(FSP) , section 4: Numerical examples illustrated with solutions and section 5: conclusion .

2.0. Preliminaries

Basic notations and preliminary results are referred from [1,2,3]

.Definition 2.1

A fuzzy set $A = \{(x, \mu_A(x)) : x \in X\}$ is defined for $x \in X$ with respect to the membership function μ_A where μ_A is defined by $\mu_A : X \rightarrow [0,1]$

Definition 2.1.1

A fuzzy number $\tilde{A} = (a,b,c)$ is said to **triangular fuzzy number** if its membership function is defined by

$$\mu_{\tilde{A}}(x) = \begin{cases} \frac{x-a}{b-a}, & a \leq x \leq b \\ \frac{x-c}{b-c}, & b \leq x \leq c \\ 0, & x > c \end{cases}$$

Definition 2.1.2

A **ranking function** is an efficient method for ordering the fuzzy numbers and is defined by $\mathfrak{R}(\tilde{A}) = \frac{a+2b+c}{4}$ where $\tilde{A} = (a,b,c)$

Fuzzy arithmetic operations 2.1.3

Let $\tilde{A} = (a,b,c)$ and $\tilde{B} = (e,f,g)$ then

1. $\tilde{A} \oplus \tilde{B} = (a+e, b+f, c+g)$
2. $-\tilde{A} = (-c, -b, -a)$
3. $\tilde{A} \ominus \tilde{B} = (a-g, b-f, c-e)$
4. Let $\tilde{A} = (a_1, a_2, a_3)$ and $\tilde{B} = (b_1, b_2, b_3)$ then
 - i) $\tilde{A} \approx \tilde{B}$ iff $a_i = b_i$, ii) $\tilde{A} \leq \tilde{B}$ iff $a_i \leq b_i$, iii) $\tilde{A} \geq \tilde{B}$ iff $a_i \geq b_i$, iv) $\tilde{A} \geq 0$ iff $a_i \geq 0$

3. Application of ranking functions to solve fuzzy sequencing problem

3.1 Algorithm for solving fuzzy sequencing problem

3.1.1 Processing ‘n’ jobs through two machines

The simplest possible fuzzy sequencing decision problem is that of ‘n’ jobs two machine fuzzy sequencing problem is to determine the sequence in which ‘n’ jobs should be processed through two machines so as to minimize the total elapsed time T. This type of problem can be completely described as :

- i) only two machines \tilde{A} and \tilde{B} are involved
- ii) each job is processed in the order AB, and
- iii) the expected fuzzy processing time $\tilde{A}_i = (a_i, b_i, c_i)$ and $\tilde{B}_i = (x_i, y_i, z_i)$ where

$i = 1, 2, 3 \dots n$ are known as given below:

job	J1	J2	J3	Jn
\tilde{A}_i	(a_1, b_1, c_1)	(a_2, b_2, c_2)	(a_3, b_3, c_3)	(a_n, b_n, c_n)
\tilde{B}_i	(x_1, y_1, z_1)	(x_2, y_2, z_2)	(x_3, y_3, z_3)	(x_n, y_n, z_n)

The procedure for the solution of the above problem is described as follows:

Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem

Step 2: the optimal sequence for the crisp sequencing problem is determined using crisp sequencing algorithm

Step 3: After finding the optimal sequence as stated above, the total elapsed fuzzy time and also the fuzzy idle times on machines \tilde{A} and \tilde{B} are determined as follows:

Step 4: **Total elapsed fuzzy time** = the fuzzy time between starting the first job in the optimal sequence on machine \tilde{A} and completing the last job in the optimal sequence on machine \tilde{B} .

Step 5: **Fuzzy idle time on machine \tilde{A}** = (fuzzy time when the last job in the optimal sequences is completed on Machine \tilde{B}) – (fuzzy time when the last job in the optimal sequence completed on machine \tilde{A})

Step 6: **Fuzzy idle time on machine \tilde{B}** = (fuzzy time when the first job in the optimal sequence completed on machine \tilde{A}) + $\sum_{k=2}^n [(fuzzy\ time\ when\ k^{th}\ job\ starts\ on\ machine\ \tilde{B}) - (fuzzy\ time\ k - 1)^{st}\ job\ finished\ on\ machine\ \tilde{B})]$

3.1.2 Processing ‘n’ jobs through three machines

This type of problem can be completely described as :

- i) only two machines \tilde{A} , \tilde{B} and \tilde{C} are involved
- ii) each job is processed in the order $\tilde{A}\tilde{B}\tilde{C}$
- iii) no passing of jobs is permitted, and
- iii) the expected fuzzy processing time $\tilde{A}_i = (a_i, b_i, c_i)$, $\tilde{B}_i = (x_i, y_i, z_i)$, $\tilde{C}_i = (e_i, f_i, g_i)$

where $i = 1, 2, 3 \dots n$ are known as given below:

job	J1	J2	J3	Jn
\tilde{A}_i	(a_1, b_1, c_1)	(a_2, b_2, c_2)	(a_3, b_3, c_3)	(a_n, b_n, c_n)
\tilde{B}_i	(x_1, y_1, z_1)	(x_2, y_2, z_2)	(x_3, y_3, z_3)	(x_n, y_n, z_n)
\tilde{C}_i	(e_1, f_1, g_1)	(e_2, f_2, g_2)	(e_3, f_3, g_3)	(e_n, f_n, g_n)

The procedure for the solution of the above problem is described as follows:

Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem

Step 2: the optimal sequence for the crisp sequencing problem of Processing ‘n’ jobs through three machines is determined using crisp sequencing algorithm.

The resulting optimal sequence will also be optimal for the original problem of 3 machines and n jobs. The total elapsed fuzzy time and also the fuzzy idle times on machines \tilde{A} , \tilde{B} and \tilde{C} are determined as follows:

Step 3: **Total elapsed fuzzy time** = the fuzzy time between starting the first job in the optimal sequence on machine \tilde{A} and completing the last job in the optimal sequence on machine \tilde{C} .

Step 4: **Fuzzy idle time on machine \tilde{A}** = (fuzzy time when the job J1 is completed on Machine \tilde{C}) – (fuzzy time when the last job is completed on machine \tilde{A})

Step 5: **Fuzzy idle time on machine \tilde{B}** = (fuzzy time when the first job \tilde{J}_3 is completed on machine \tilde{A}) + $\sum_{k=2}^n$ [(fuzzy time when k^{th} job on machine \tilde{B}) – (fuzzy time out for $(k - 1)^{st}$ job on machine \tilde{B})] + [fuzzy time last job is completed on \tilde{C} – fuzzy time last job is completed on \tilde{B}]

Step 6: **Fuzzy idle time on machine \tilde{C}** = (fuzzy time when the first job \tilde{J}_3 is completed on machine \tilde{B}) + $\sum_{k=2}^n$ [(fuzzy time when k^{th} job on machine \tilde{C}) – (fuzzy time out for $(k - 1)^{st}$ job on machine \tilde{C})]

3.1.3 Processing ‘n’ jobs through m machines

This type of problem can be completely described as :

- i) there are n jobs denoted by J1, J2, J3, ..., Jn to be performed
- ii) each job is processed through m machines $\tilde{A}_1, \tilde{A}_2, \tilde{A}_3, \dots, \tilde{A}_m$ in the order $\tilde{A}_1 \tilde{A}_2 \tilde{A}_3, \dots, \tilde{A}_m$
- iii) no passing of jobs is permitted
- iv) the expected fuzzy processing time are known as given below:

Job	machine fuzzy time for n jobs and m machines			
	Machines			
	\tilde{A}_1	\tilde{A}_2	$\tilde{A}_3 \dots \dots \dots$	\tilde{A}_m
J1	(a ₁₁ , b ₁₁ , c ₁₁)	(a ₁₂ , b ₁₂ , c ₁₂)	(a ₁₃ , b ₁₃ , c ₁₃)(a _{1m} , b _{1m} , c _{1m})
J2	(a ₂₁ , b ₂₁ , c ₂₁)	(a ₂₂ , b ₂₂ , c ₂₂)	(a ₂₃ , b ₂₃ , c ₂₃)(a _{2m} , b _{2m} , c _{2m})

$$J_3 \quad (a_{31}, b_{31}, c_{31}) \quad (a_{32}, b_{32}, c_{32}) \quad (a_{33}, b_{33}, c_{33}) \quad \dots \quad (a_{3m}, b_{3m}, c_{3m})$$

$$J_i \quad (a_{i1}, b_{i1}, c_{i1}) \quad (a_{i2}, b_{i2}, c_{i2}) \quad (a_{i3}, b_{i3}, c_{i3}) \quad \dots \quad (a_{im}, b_{im}, c_{im})$$

$$J_n \quad (a_{n1}, b_{n1}, c_{n1}) \quad (a_{n2}, b_{n2}, c_{n2}) \quad (a_{n3}, b_{n3}, c_{n3}) \quad \dots \quad (a_{nm}, b_{nm}, c_{nm})$$

The procedure for the solution of the above problem is described as follows:

Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem

Step 2: the optimal sequence for the crisp sequencing problem of Processing ‘n’ jobs through m machines is determined using crisp sequencing algorithm.

The resulting optimal sequence will also be optimal for the original problem. The total elapsed fuzzy time and also the fuzzy idle times on machines are also determined

4.0. Numerical examples illustrated with solutions using triangular fuzzy numbers

4.1 Fuzzy Sequencing for 5 jobs on 2 machines

Ex:1 A book binder has one printing press, one binding machine and manuscripts of a number of different books. The time required to perform the printing and binding operation for each book are shown below. We wish to determine the order in which books should be processed, in order to minimize the total time(in hrs) required to turn out all the books

Books: \tilde{B}_1	\tilde{B}_2	\tilde{B}_3	\tilde{B}_4	\tilde{B}_5
Printing time: (5,10,15)	(1,2,3)	(10,20,22)	(2,5,12)	(10,20,30)
Binding time: (3,4,5)	(5,10,23)	(7,16,17)	(10,15,24)	(4,9,10)

Solution:

Using ranking function for triangular fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm.

The sequence of the jobs is given by

B2	B4	B3	B5	B1
----	----	----	----	----

The fuzzy optimum time for completing all the books and the idle time for printing and binding is given in the following table:

Books	Printing	Printing	Binding	Binding	Idle time for printing	Idle time For binding
	In time	Out time	In time	Out time		
B2	(0,0,0)	(1,2,3)	(1,2,3)	(6,12,26)	-	(1,2,3)
B4	(1,2,3)	(3,7,15)	(6,12,26)	(16,27,50)	-	-
B3	(3,7,15)	(13,27,37)	(16,27,50)	(23,43,67)	-	-
B5	(13,27,37)	(23,47,67)	(23,47,67)	(27,56,77)	-	(-44,4,44)
B1	(23,47,67)	(28,57,82)	(28,57,82)	(31,61,87)	(-51,4,59)	(-49,1,55)
				Total	(-51,4,59)	(-92,7,102)

The optimum (minimum) time required to turn out all the books is (31,61,87) hrs

The idle time for printing is (-51,4,59) hours

The idle time for binding is (-92,7,102) hours

4.2 Fuzzy Sequencing for 5 jobs on 3 machines

Ex:2

Job	:	J1	J2	J3	J4	J5
Machine \tilde{A} :	(4,5,6)	(6,7,8)	(5,6,7)	(8,9,10)	(4,5,6)	
Machine \tilde{B} :	(1,2,3)	(1,1,1)	(3,4,5)	(4,5,6)	(2,3,4)	
Machine \tilde{C} :	(2,3,4)	(5,7,9)	(4,5,6)	(5,6,7)	(6,7,8)	

Solution:

Using ranking function for triangular fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

The sequence of the jobs is given by

J2	J5	J4	J3	J1
----	----	----	----	----

The fuzzy optimum time for completing all the jobs and the idle time for the two machines is given in the following table:

Job	Machine \tilde{A}	Machine \tilde{A}	Machine \tilde{B}	Machine \tilde{B}	Machine \tilde{C}	Machine \tilde{C}	Idle time \tilde{A}	Idle time \tilde{B}	Idle time \tilde{C}
	In time	Out time	In time	Out time	In time	Out time			
J ⁻ 2	(0,0,0)	(6,7,8)	(6,7,8)	(7,8,9)	(7,8,9)	(12,15,18)	-	(6,7,8)	(7,8,9)
J ⁻ 5	(6,7,8)	(10,12,14)	(10,12,14)	(12,15,18)	(12,15,18)	(18,22,26)	-	(1,4,7)	(-4,4,12)
J ⁻ 4	(10,12,14)	(18,21,24)	(18,21,24)	(22,26,30)	(22,26,30)	(27,32,37)	-	(0,6,12)	-
J ⁻ 3	(18,21,24)	(23,27,31)	(23,27,31)	(26,31,36)	(22,32,37)	(31,37,43)	-	(-7,1,9)	-
J ⁻ 1	(23,27,31)	(27,32,37)	(27,32,37)	(28,34,40)	(31,37,43)	(33,40,47)	(-4,8,20)	(-9,1,11)	-
								(-7,6,19)	
						Total	(-4,8,20)	(-16,25,66)	(3,12,21)

The optimum (minimum) time required to finish all the jobs is **(33,40,47)** hours

The idle time for machines \tilde{A} is **(-16,25,66)** hours

The idle time for machines \tilde{B} is **(3,12,21)** hours

4.3 Fuzzy Sequencing for 4 jobs on 5 machines

Ex:3

	Machine				
	\tilde{A}	\tilde{B}	\tilde{C}	\tilde{D}	\tilde{E}
J1	(8,9,10)	(6,7,8)	(3,4,5)	(4,5,6)	(10,11,12)
Job J2	(7,8,9)	(7,8,9)	(5,6,7)	(6,7,8)	(11,12,13)
J3	(6,7,8)	(5,6,7)	(6,7,8)	(7,8,9)	(9,10,11)
J4	(9,10,11)	(4,5,6)	(4,5,6)	(3,4,5)	(7,8,9)

Solution:

Using ranking function for triangular fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

The sequence of the jobs is given by

J1	J3	J2	J4
----	----	----	----

The fuzzy optimum time for completing all the jobs and the idle time for the two machines is given in the following table:

Job	Machine \tilde{A}	Machine \tilde{A}	Machine \tilde{B}	Machine \tilde{B}	Machine \tilde{C}	Machine \tilde{C}	Machine \tilde{D}	Machine \tilde{D}	Machine \tilde{E}	Machine \tilde{E}
	In time	Out time	In time	Out time	In time	Out time	Out time	In time	In time	In time
J1	(0,0,0)	(8,9,10)	(8,9,10)	(14,16,18)	(14,16,18)	(17,20,23)	(17,20,23)	(21,25,29)	(21,25,29)	(31,36,41)
J3	(8,9,10)	(14,16,18)	(14,16,18)	(19,22,25)	(19,22,25)	(25,29,33)	(25,29,33)	(32,37,42)	(32,37,42)	(41,47,53)
J2	(14,16,18)	(21,24,27)	(21,24,27)	(28,32,36)	(28,32,36)	(33,38,43)	(33,38,43)	(39,45,51)	(41,47,53)	(52,59,66)
J4	(21,24,27)	(30,34,38)	(30,3,38)	(34,39,44)	(34,39,44)	(38,44,50)	(39,45,51)	(42,49,56)	(52,59,66)	(59,67,75)

	Idle time \tilde{A}	Idle time \tilde{B}	Idle time \tilde{C}	Idle time \tilde{D}	Idle time \tilde{E}
	-	(8,9,10)	(14,16,18)	(17,20,23)	(2,25,29)
	-	-	(-4,2,8)	(-4,4,12)	(-9,1,11)
	-	(-4,2,8)	(-5,3,11)	(-9,1,11)	-
	(21,33,45)	(-6,2,10)	(-9,1,11)	-	-
		(15,28,41)	(9,23,37)	(3,18,33)	
Total	(21,33,45)	(13,41,69)	(5,45,85)	(7,43,79)	(12,26,40)

The optimum (minimum) time required to finish all the jobs is (59,67,75)hours

The idle time for machines \tilde{A} is (21,33,45)hours

The idle time for machines \tilde{B} is (13,41,69) hours

The idle time for machines \tilde{C} is (5,45,85) hours

The idle time for machines \tilde{D} is (7,43,79)hours

The idle time for machines \tilde{E} is (12,26,40)hours

4.3 Graphical method

Ex.:4	Machine			
Job J1	A	B	C	D
Job J2	D	B	A	C
Machine	A	B	C	D
Job J1	(3,4,5)	(5,6,7)	(6,7,8)	(2,3,4)
Job J2	(3,4,5)	(6,7,8)	(4,5,6)	(2,3,4)

Solution:

Using ranking function for triangular fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

4.4 Special cases:

There is no restrictions on the fuzzy numbers i.e the fuzzy numbers needed not be non-negative numbers .Hence the optimal sequence and the minimum elapsed time for the triangular fuzzy number which is not a non-negative fuzzy number can also be determined.

5 Conclusion

Fuzzy sequencing problem is solved by classical approach after defuzzification , which is easy to understand , helps to formulate uncertainty in actual environment and also serves as application for the decision makers in real life situation.

References

- [1] M. Jayalakshmi and P.Pandian – A new method for finding an optimal fuzzy Solution for fully fuzzy linear programming problem –International Journal of Engineering research and applications – vol 2, Issue 4 , July- August 2012, pp 247-254
- [2] Amit kumar,Pushpinder singh, Pampreet Kaur, Amar Preet Kaur- Generalized Simplex algorithm to olve fuzzy linear programming problem with ranking of Generalized fuzzy numbers- Turkish Journal of fuzzy system, vol 1, No.2, Pp80-103,2010.
- [3] Amit kumar,Pushpinder singh, Pampreet Kaur, Amar Preet Kaur- A new method for solving fully fuzzy linear programming problem- Applied mathematical modeling 35(2011) 817-823.